


**ROTOR**  
BOTTOM BRACKET  
COMPATIBILITY



**ROTOR**  
CRANK  
COMPATIBILITY

		THREADED BB		NON THREADED BB							
		<b>W</b> = 68 mm <b>BSA</b>	<b>W</b> = 70 mm <b>ITA</b>	<b>D</b> = 37 mm <b>BB90</b>	<b>D</b> = 41 mm	<b>D</b> = 42 mm		<b>D</b> = 46 mm			
				<b>W</b> = 86 mm <b>BB86</b>	<b>W</b> = 68 mm <b>BB30</b>	<b>W</b> = 79 mm <b>BBRight California</b>	<b>W</b> = 68 mm <b>PressFit30</b>	<b>W</b> = 79 mm <b>BBRight PF</b>	<b>W</b> = 86 mm <b>BB386EVO</b>		
24 mm SPINDLE	 BB1 BSA SABB BSA TRACK BSA   3D24 (All Shimano compatible)	 BB1 ITA SABB ITA TRACK BSA   3D24 (All Shimano compatible)	 3D24 (All Shimano compatible)	 Press Fit 4124   3D24 (All Shimano compatible)	 BB30 to 24 Road   3D24 (All Shimano compatible)	 BB30 BEARING KIT   3D+ 3D30 FLOW POWER	 BB30 BEARING KIT   3D+ 3D30 FLOW POWER	 Press Fit 4624 Road   3D24 (All Shimano compatible)	 BBRight 4624   3D24 (All Shimano compatible)		24 mm SPINDLE
	 BSA30   3D+ 3D30 FLOW POWER	 ITA30   3D+ 3D30 FLOW POWER		 Press Fit 4130   3D+ 3D30 FLOW POWER	 BB30 BEARING KIT   3D+ 3D30 FLOW POWER	 BB30 BEARING KIT   3D+ 3D30 FLOW POWER	 Press Fit 4630   3D+ 3D30 FLOW POWER	 Press Fit 4630   3D+ 3D30 FLOW POWER	 Press Fit 4630   3D+ 3D30 FLOW POWER		